


# SECTION 3

## WOOD GRAIN LAMINATES




LM4001

Floating Floor End Stop  
Used when butting floating floors to walls, patio doors or other flooring materials of similar heights such as hardwood or ceramic tile.




LM4002

Expansion Joint (divider) for Floating Floors. Used when installing large areas of floating floors as an expansion joint. Overhang allows expansion of floors and eliminates buckling. Should be used for any installation greater than 12' in any one direction.




LM4003

Floating Floor Reducer.  
Reduces from 5/16" to 1/8" floor. Used when butting floating floors up to 1/8" tile or resilient sheet goods.




LM4005

Floating Floor Reducer.  
Reduces from 5/16" to 0" floor. Used when butting floating floors on top of existing floors or subfloor.




LM4006

Reduces from laminate floor to sub floor or to existing floor. Reduces from 9/16" to 0" Aluminum strength and durability. Woodgrain finish surface is treated with an aluminum oxide finish. Works with LM3003 (1/2") extended track woodgrain and satin finishes





LM4004

Floating Floor Stairnosing.  
Finishes edge of stair. For nosing applications use LM3002.




LM3001

The easy to install LM3001 snap-in track design, provides a unique sleek low profile to enhance any laminate floor. Made of rigid PVC.




LM3002

LM3002 track to be used for stair nose applications. Flange adds strength and stability. Staggered drilled Made of rigid PVC.




LM3003

LM3003 track to be used for 10mm laminate floors. Track provides secure grip of moulding for greater durability and safety. Flange adds extra strength and stability. Made of PVC.




LM3004

LM3004 track to be used for 12.5mm laminate floors. Track provides secure grip of moulding for greater durability and safety. Flange adds extra strength and stability. Made of PVC.



The mouldings are made of aluminum providing incomparable strength and durability. In addition the wood grain surface is treated with an aluminum oxide finish that increases surface hardness up to 3 times more over other sealers and coatings.



BEECH

CHERRY

MAPLE

OAK

RED OAK

WALNUT

Wood Grain Finish Laminate Mouldings available in OAK, ROK, BCH, MAP, CHY, WAL