

MATERIAL SAFETY DATA SHEET

WOOD FLOOR MOULDINGS

The data presented here applies to all **Loxreen** Wood Floor Mouldings. Although profiles vary in terms of physical or other characteristics, safety and handling precautions are similar for all.

SECTION I: PRODUCT IDENTIFICATION

Manufacturer's Name: Loxreen Flooring Group
Address: 5720 Ambler Dr., Mississauga, ON, CANADA, L4W 2B1
Phone: 905-629-4875

SECTION II: COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Family: Red Oak
CAS Registry Number: N/A

SECTION III: PHYSICAL DATA

Materials At Normal Conditions: Solid
Appearance And Odor: A Granular Solid
Acidity Alkalinity: N/A
Vapor Pressure: N/A
Melting Point: 390 – 500 °F (degrees Fahrenheit)
Specific Gravity: 0.5 to 1 [H₂O = 1]
Boiling Point: N/A
Solubility In Water (% by weight): Insoluble

SECTION IV: PREVENTATIVE MEASURES

Personal Protective Equipment

Protective Gloves: Recommended to reduce skin contact, except where moving machinery parts expose fingers to hazards.

Eye Protection: Safety Glasses, under dusting conditions

Respiratory Equipment: Approved dust respirator, under dusting conditions

Other Protective Equipment: Recommend the use of clean body-covering work clothing to reduce exposure of skin to wood dust.

Local Exhaust: To meet TLV requirements. Due to the explosive potential of wood dust when suspended in air, precautions should be taken to prevent sparks or other ignition sources in ventilation equipment. Use of totally enclosed motors is recommended.

SECTION V: TOXICOLOGICAL PROPERTIES

Inhalation:	Not likely
Ingestion:	Not likely
Skin:	May cause irritation
Eyes:	Not likely

SECTION VI: FIRST AID MEASURES

For Skin Contact:	Remove particles by thoroughly washing with soap and water.
For Inhalation:	If irritation from exposure to process fumes persists, remove affected individual(s) and call a physician.

SECTION VII: FIRE AND EXPLOSION DATA

Flash Point:	N/A
Auto Ignition Temperature:	N/A
Extinguishing Media:	Extinguish as if an ordinary combustible (NFPA Class A material) using water (which is most effective), or ABS dry chemical, or AFFF or protein foam.
Special Fire Fighting Procedures:	Positive pressure self-contained breathing apparatus (SCBA) is suggested during and immediately after a fire.
Unusual Fire & Explosion Hazard:	Thermal decomposition liberates hydrogen chloride in addition to typical combustion gases such as carbon monoxide.

SECTION VIII: REACTIVITY

Stability:	Stable
Incompatibility:	N/A
Conditions To Avoid:	N/A

SECTION IX: ENVIRONMENTAL

Spill Or Leak Procedures:	Vacuum or sweep into a closed container for reuse or disposal. Dispose of or incinerate in accordance with local regulations.
Waste Disposal Methods:	Dispose of or incinerate in accordance with local regulations at a licensed/permitted facility. Incineration may yield hydrogen chloride gas.

SECTION X: ADDITIONAL INFORMATION

N/A

SECTION XI: PREPARATION INFORMATION

MSDS Prepared By: Loxcreen Flooring Group

Phone Number: 1 – 800 – 265 – 2977

Date: August 4, 2009

While Loxcreen Flooring Group, believes that the data contained herein is accurate and derived from qualified sources, the data is not to be taken as a warranty or representation for which Loxcreen Flooring Group assumes legal responsibility. It is offered solely for your consideration, investigation and verification. Any use of this data and information must be determined by the user to be in accordance with applicable Federal, State and local laws and regulations.